

USB - TTL / UART / RS232 adapter with PL2303HX chipset

This adapter enables access to the Raspberry Pi or a microcontroller via a terminal programme on a PC or Mac. The adapter also provides a power supply.

Product number AUSB-TTL

Weight 0.01kg



Product description

This adapter enables access to the Raspberry Pi or a microcontroller via a terminal programme on a PC or Mac. The adapter also provides a power supply.

Technical data

- Chipset: Prolific PL2303HX (Rev. HXA)
- Pins accessible via pin header (RM 2.54):
 - 3.3V
 - TXD
 - RXD
 - Ground / GND
 - 5.0V
- Dimensions:
 - Total with connections (USB / pin header): 52 x 15 x 7 mm
 - PCB only: 31 x 15 x 5 mm
- 3 status LEDs (operation, TX, RX)
- Compatible for the following operating systems:
 - Windows 2000 / XP / Server 2003 / Vista / Windows 7 / Server 2008/R2 32 & 64 bit - Not Windows 8 / 8.1 compatible!
 - Mac OS X 10.9 Mavericks (64-bit), Mac OS X 10.8 Mountain Lion (64-bit), Mac OS X 10.7 Lion (32-bit & 64-bit), Mac OS X 10.6 Snow Leopard (32-bit & 64-bit)
 - Linux - Depending on the distribution used!
 - tested with the Raspberry Pi under Raspbian - Included here without driver installation.

Downloads

[Drivers and installation instructions for Windows & Mac OS](#)

Product properties

Gross Weight (kg)	0.01
Zolltarifnummer	84718000
Country of Origin	China
Product ID	AUSB-TTL
Manufacturer ID	AUSB-TTL
Brand	BerryBase
EAN	4251266703228
Compatibility	Raspberry Pi Pico, Raspberry Pi 4B, Raspberry Pi 3B+, Raspberry Pi Zero, Raspberry Pi Zero W, Raspberry Pi 3B, Raspberry Pi 3A+, Raspberry Pi Zero WH

More images

